



# Universal



## ALFs DÄCKIMPORT ÖDENÄS



### UNIVERSAL® TIRE SPECS

SIZE	PHOTO	WW WIDTH	CONSTRUCTION	LOAD CAPACITY	TREAD WIDTH	OVERALL DIAMETER
28x3 CL Ribbed	D, F	AW* & Black	4 Ply Nylon	450 @ 55 psi	2.50	28.00
28x3 CL Smooth**	B	AW* & Black	4 Ply Nylon	450 @ 55 psi	2.50	28.00
28x3 CL Smooth**	C	All Gray*	4 Ply Nylon	450 @ 55 psi	2.50	28.00
30x3 <sup>1/2</sup> CL T-Driver	A	Black only	4 Ply Nylon	650 @ 60 psi	3.00	32.00
30x3 <sup>1/2</sup> CL Ribbed	D, F	AW* & Black	4 Ply Nylon	500 @ 60 psi	2.75	30.25
30x3 <sup>1/2</sup> CL Ribbed	G	All Gray*	4 Ply Nylon	500 @ 60 psi	2.75	30.25
30x3 <sup>1/2</sup> CL Smooth**	B	AW* & Black	4 Ply Nylon	500 @ 60 psi	2.75	30.25
30x3 <sup>1/2</sup> CL Smooth**	C	All Gray*	4 Ply Nylon	500 @ 60 psi	2.75	30.25
30x3 CL T-Driver	A	Black only	4 Ply Nylon	450 @ 50 psi	2.50	30.00
30x3 CL Ribbed	D, F	AW* & Black	4 Ply Nylon	450 @ 50 psi	2.50	30.00
30x3 CL Ribbed	G	All Gray*	4 Ply Nylon	450 @ 50 psi	2.50	30.00
30x3 CL Smooth**	B	AW* & Black	4 Ply Nylon	450 @ 50 psi	2.50	30.00
30x3 CL Smooth**	C	All Gray*	4 Ply Nylon	450 @ 50 psi	2.50	30.00
36x3 <sup>1/2</sup> /37x4 CL	D, F, G		4 Ply Nylon	875 @ 65 psi	2.60	36.20
31x4 SS	D, F, G		4 Ply Nylon	1000 @ 60 psi	3.00	32.00
32x4 SS	D, F, G		4 Ply Nyl./6PR	1050 @ 60 psi	3.00	33.50
33x4 SS	D, F, G		4 Ply Nylon	1050 @ 60 psi	3.25	34.75
33x4 <sup>1/2</sup> SS	D, F, G		4 Ply Nyl./6PR	1250 @ 60 psi	3.38	33.25
33x5 SS	E°, F	3"*	4 Ply Poly	1100 @ 60 psi	4.00	34.25
34x4 SS	D, F, G		4 Ply Nyl./6PR	1100 @ 60 psi	3.00	35.75
34x4 <sup>1/2</sup> SS	D, F, G		4 Ply Nyl./6PR	1250 @ 60 psi	3.50	35.50
35x5 SS	D, F, G		6 Ply Nylon	1800 @ 70 psi	4.25	37.00
36x4 SS	D, F, G		4 Ply Nyl./6PR	1100 @ 60 psi	3.00	37.00
36x4 <sup>1/2</sup> SS	D, F, G		4 Ply Nyl./6PR	1250 @ 60 psi	3.50	36.50
36x5 SS	D, F, G		6 Ply Nylon	1800 @ 70 psi	4.25	37.75
37x4 <sup>1/2</sup> SS	D, F, G		4 Ply Nyl./6PR	1250 @ 60 psi	3.50	36.50
37x5 SS	D, F, G		6 Ply Nylon	1800 @ 70 psi	4.50	38.00
41x4 <sup>1/2</sup> SS	D, F, G		4 Ply Nyl./6PR	1450 @ 65 psi	4.00	41.00
43x5 SS	D, F, G		4 Ply Nyl./6PR	1800 @ 70 psi	4.25	43.50
750-14	H	2 <sup>1/4</sup> "	4 Ply Poly	1500 @ 32 psi	4.40	27.60
800-14	H	1", 2 <sup>1/4</sup> "	4 Ply Poly	1620 @ 32 psi	4.60	28.25
185HR15	L	Black	Poly/Steel	1356 @ 35 psi	5.50	26.50
185HR15	M	5/8"	Poly/Steel	1356 @ 35 psi	5.50	26.50
670-15	I	2 <sup>11/16</sup> "	4 Ply Poly	1450 @ 32 psi	4.90	28.40
670-15	I	3 <sup>1/4</sup> "	4 Ply Poly	1450 @ 32 psi	4.90	28.40
710-15	J	2 <sup>3/4</sup> , 3"	4 Ply Poly	1550 @ 32 psi	4.60	28.95
760-15	J	3"	4 Ply Poly	1710 @ 32 psi	5.00	29.70
820-15	J	2 <sup>1/4</sup> , 3 <sup>1/2</sup> "	4 Ply Poly	1920 @ 32 psi	5.40	30.40
185R16 S	L	Black only	Poly/Steel	1433 @ 35 psi	5.50	26.75
475/500-19	K	Black only	4 Ply Poly	900 @ 32 psi	4.00	29.50
450/475-21	K	Black only	4 Ply Poly	900 @ 32 psi	3.90	30.75



# TELEFON 0322-53437

CL=Clincher SS=Straight side AW=All White \*All white & All Gray may require special order \*\*Smooth tread clincher tires may provide poor mileage. \*Tread E° whitewall is only available in 33x5 size. These tires are designed for vehicles manufactured prior to 1976.